



CO/60008



CO/60010

Conductivity meters, portable, Mettler F3, FiveGO

Ideally suited for mobile applications in the laboratory, at-line, or outdoors, the new FiveGo portable conductivity meter provides high performance and measurements at the click of a button. The robust and waterproof design makes the FiveGo instruments the perfect companion to get reliable measurement data even in harsh conditions. Time is an ever more valuable asset, but thanks to the FiveGo's intuitive operation, robust design and extensive memory functions, you can maximize your time spent measuring instead of dealing with complex system and measurement setups. Meters to measure pH or dissolved Oxygen, are also available in the FiveGo range.

- Large display with simple menu, measurements can be made with just a few clicks.
- Ergonomic designed for either left or right handed use, with a foldable foot stand which provides optimal viewing while situated on a lab bench.
- Waterproof protection to IP67, with carry case
- Optimally designed for mobile measurements in a wide range of workplaces, including Environment, Academia, Food and Beverage, Agriculture and Industry

| Technical Specifications | |
|------------------------------------------------|-------------------------------------------------------------------------------------------------|
| Measuring range | 0.00µS/cm - 200mS/cm (conductivity) 1.01 mg/l -200 g/l (TDS) 0°C to 100°C (32°F to 212°F) |
| Resolution | Automatic range 0.1°C |
| Accuracy | ±0.5% of the measured value ± 0.5°C |
| Automatic and manual end point recording | Yes |
| Acoustic end point signal | Yes |
| Visual end point signal | Yes |
| Temperature compensation reference temperature | Linear 0.00%/°C to 10.00%/°C 20 and 25°C |
| Calibration | 1 point, 3 predefined standards |
| Memory size | 200 measurements, current calibration |
| Sensor input | LTW 7-pin |
| IP Protection | IP67 |
| Power supply | 4 x AAA batteries |
| Operating hours | >200 hours |
| Display | 3.1 segmented LCD |
| Housing | ABS |
| Dimensions | 188 x 77 x 33mm |
| Weight | 0.26kg |

| Cat. No. | Description |
|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CO/60008 | Conductivity meter FiveGo F3 without electrode, for applications that require a specific sensor not included in a kit |
| CO/60010 | Conductivity meter FiveGo F3 Standard kit, comprising of meter with LE703 IP67 sensor, for applications involving aqueous samples with mid to high conductivity |
| CO/60012 | Conductivity meter FiveGo F3 Field kit, comprising of meter with LE703 IP67 sensor, for applications involving aqueous samples with mid to high conductivity in the field, with carrying case |

Notes