pH meter, Jenway 550

Model 550 hand-held general purpose portable pH and temperature meter offering 2 point pH calibration and automatic buffer recognition. This model simultaneously displays both the temperature compensated pH readings and temperature. This small, lightweight meter has an LCD display encompassed in a splash proof housing.

- Simultaneously displays pH and temperature
- Automatic calibration
- Manual or Automatic Temperature Compensation (ATC)
- Auto shut off 10 minutes
- 5000 hours battery life
- 2 year warranty

This meter is supplied ready to use with an epoxy bodied electrode (924 001), a temperature probe (170 101) and buffers in a handy carry case.

PH/25010

PH/25720

Technical Specifications

Model	550
Type	pH and temperature
Waterproof	No (IP65)
pH Range	0 to 14
pH Resolution	0.01
pH Accuracy	± 0.05
ATC	0 to 60°C
Temperature Range	0 to 100°C
Temperature Resolution	0.1°C
Temperature Accuracy	± 0.5°C
No. of Calibration Points	2
Automatic Buffer Recognition	Yes
Auto Shut Off	10 mins
Operating Temperature	0 to 50°C
Battery Life (hours)	5000
pH Connector	BNC
Temperature Connector	3.5mm jack
Dimensions (l x w x d)	128 x 56 x 25mm
Weight	130g

Cat. No.	Code	Description
PH/25010	550 271	pH meter, model 550
PH/25710	924 001	Replacement electrode
PH/25720	170 101	Replacement ATC probe for model 550

Notes