



PW/46322

Pipette/burette rinsing set, automatic

KartellLABWARE

High quality and high speed solves the problem of washing pipettes up to 600mm long and Mohr burettes quickly and safely. Indispensable in the laboratory where radioactive, caustic and toxic materials are in use. The polyethylene rinser fills via the spray nozzle situated on the top rim. This eliminates back-syphoning as the water inlet is located above and away from any contaminated waters. Contaminated waters will syphon out totally, once the syphon point at the top of the rinser has been reached, via the large diameter drain situated at the lowest point, before refilling automatically. During washing the pipettes/burettes are housed in specially designed baskets which minimises breakages and is particularly safe as it buffers the tips of pipettes against the soft polyethylene base. Since soaking takes the longest time, two or three baskets of pipettes/burettes can be soaking in their jars whilst another basket full is being washed in the rinser. Low water flow rate is not a problem but it is best to adjust the flow for a cycle of about 90 secs.

Suggested basic set for:

| Pipettes | Burettes |
|--------------|--------------|
| 1 x PW/46324 | 1 x PW/46322 |
| 2 x PW/46328 | 2 x PW/46328 |
| 1 x PW/46326 | 2 x PW/46330 |
| | 1 x PW/46326 |

| Cat. No. | Code | Description | Dia. x Height, mm |
|----------|------|--|-------------------|
| PW/46322 | 215 | Burette rinser | 165 x 750 |
| PW/46324 | 217 | Pipette rinser | 165 x 650 |
| PW/46326 | 218 | Jar | 165 x 650 |
| PW/46328 | 219 | Basket | 130 x 300 |
| PW/46330 | 1219 | Extension handle for use with PW/46328 | |



BA/3601

Baskets, pipette, HDPE

Rugged, resilient baskets cushion pipettes. Perforated screen is recessed into the base 20mm for complete drainage. With handle. Basket O.D. 133 mm.

| Cat. No. | Code | Height, mm |
|----------|-----------|------------|
| BA/36010 | 5241-0020 | 375 |
| BA/36012 | 5241-0040 | 578 |
| BA/36014 | 5241-0050 | 781 |



PC/84

Pipette sterilising cans

Cylindrical pipette cans manufactured from stainless steel. Can be steam sterilised at 120°C and will withstand dry heat temperatures of up to 180°C.

| Cat. No. | Overall length | Diameter |
|----------|----------------|----------|
| PC/84002 | 230mm | 64mm |
| PC/84004 | 407mm | 64mm |
| PC/84006 | 457mm | 64mm |