

## Beakers, classic design, printed graduations, polypropylene

*Azlon*

- Azlon, designed to BS5404: Part 1 1976.
- Good chemical resistance.
- Can withstand temperatures up to 135°C.
- Graduations, indication of material and maximum heat resistance, are clearly printed using indelible solvent resistant blue ink.

| Cat. No. | Code    | Capacity, ml | Sub divs, ml | Pk Qty |
|----------|---------|--------------|--------------|--------|
| BE/16428 | BDA208P | 10           | 1            | 10     |
| BE/16434 | BDA212P | 25           | 2.5          | 10     |
| BE/16440 | BDA218P | 50           | 5            | 10     |
| BE/16446 | BDA224P | 100          | 5            | 10     |
| BE/16456 | BDA230P | 250          | 10           | 10     |
| BE/16462 | BDA234P | 400          | 20           | 10     |
| BE/16466 | BDA236P | 500          | 20           | 10     |
| BE/16470 | BDA238P | 600          | 20           | 5      |
| BE/16476 | BDA240P | 1000         | 20           | 5      |
| BE/16480 | BDA242P | 2000         | 50           | 1      |



BE/164

## Beakers, low form, printed graduations, PMP (TPX)

Conforms to ISO 7056-1981 (E) and BS5404:part 1. EEC 90/128 92/93 and FDA 21 CFR 177.1520. Crystal clear. Autoclavable. Will withstand 170°C for short periods. Permanent blue graduations. Excellent chemical resistance.

| Cat. No. | Code | Capacity, ml | Sub divs, ml | Pk Qty |
|----------|------|--------------|--------------|--------|
| BE/46834 | 1720 | 25           | 1            | 10     |
| BE/46840 | 1721 | 50           | 2            | 10     |
| BE/46846 | 1722 | 100          | 5            | 10     |
| BE/46856 | 1723 | 250          | 10           | 10     |
| BE/46866 | 1724 | 500          | 10           | 5      |
| BE/46876 | 1725 | 1000         | 20           | 1      |
| BE/46880 | 1726 | 2000         | 50           | 1      |
| BE/46884 | 1727 | 3000         | 500          | 1      |
| BE/46888 | 1728 | 5000         | 500          | 1      |



BE/468

## Beakers, PTFE

Beakers, isostatically moulded with super smooth internal finish and pouring spout. Maximum working temperature: 280°C.

| Cat. No. | Capacity, ml | Dimensions, Ht x Od, mm |
|----------|--------------|-------------------------|
| BE/40028 | 10           | 33 x 24                 |
| BE/40034 | 25           | 47 x 32                 |
| BE/40040 | 50           | 55 x 43                 |
| BE/40046 | 100          | 68 x 54                 |
| BE/40056 | 250          | 97 x 66                 |
| BE/40062 | 400          | 106 x 80                |
| BE/40066 | 500          | 125 x 80                |
| BE/40070 | 600          | 125 x 90                |
| BE/40076 | 1000         | 155 x 100               |
| BE/40080 | 2000         | 205 x 125               |



BE/400

## Beakers, metal

### Beakers, with spout, aluminium

| Cat. No. | Capacity, ml | Dia x Ht, mm |
|----------|--------------|--------------|
| BE/94256 | 250          | 67 x 76      |
| BE/94266 | 500          | 82 x 102     |
| BE/94276 | 1000         | 102 x 124    |
| BE/94280 | 2000         | 127 x 165    |
| BE/94288 | 5000         | 178 x 203    |

### Beakers, with spout, stainless steel

| Cat. No. | Capacity, ml | Dia x Ht, mm |
|----------|--------------|--------------|
| BE/94354 | 200          | 60 x 75      |
| BE/94360 | 350          | 65 x 115     |
| BE/94368 | 550          | 75 x 125     |
| BE/94371 | 700          | 75 x 165     |
| BE/94376 | 1000         | 110 x 125    |
| BE/94377 | 1250         | 100 x 165    |
| BE/94380 | 2000         | 125 x 180    |
| BE/94382 | 2500         | 150 x 160    |
| BE/94388 | 5000         | 185 x 220    |



BE/943